



24 Madison Road, Fairfield, New Jersey 07004, USA
 Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,
 email: info@jeen.com , Website: www.jeen.com

MATERIAL SAFETY DATA SHEET

U.S. Department of Labor
 Occupational Safety and Health Administration

Required under USDL Safety and Health Regulations for Ship Repairing,
 Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

Form OSHA-20
 Rev. May 72

SECTION I - MATERIAL AND MANUFACTURER IDENTIFICATION

Manufacturer's Name: JEEN INTERNATIONAL CORP.
 24 MADISON ROAD
 FAIRFIELD, NJ 07004
 Tel.# 973-439-1401

Chemtrec Emergency Telephone No: 800-424-9300
 Chemtrec Int'l Telephone No: 703-527-3887(Collect Calls Accepted)

Chemical Name and Synonyms: Ethoxylated Vegetable Oil
 Trade Name and Synonyms: **JEECHEM CA-15**

Chemical Family: Nontoxic Surfactant
 Formula: CAS # 61791-12-6

SECTION II - HAZARDOUS INGREDIENTS

BASED ON CURRENT OSHA CRITERIA, THIS PRODUCT IS CONSIDERED A NON-HAZARDOUS MATERIAL.

PAINTS, PRESERVATIVES & SOLVENTS:			ALLOYS AND METALLIC COATINGS:		
	%	TLV UNITS		%	TLV UNITS
Pigments:	-	-	Base Metal:	-	-
Catalyst:	-	-	Alloys:	-	-
Vehicle:	-	-	Metallic Coatings:	-	-
Solvents:	-	-	Filler Metal		
Additives:	-	-	Plus Coating		
Others:	-	-	or Core Flux:	-	-

HAZARDOUS MIXTURES OR OTHER LIQUIDS, SOLIDS, OR GASES:

	%	TLV UNITS
-	-	-

SECTION III - PHYSICAL DATA

BOILING POINT(°F.): N/A
 VAPOR PRESSURE (mm Hg): N/A
 VAPOR DENSITY (AIR=1): N/A
 SOLUBILITY IN WATER @25°: PARTIAL
 APPEARANCE AND ODOR: VISCOUS AMBER LIQUID, MILD FATTY ODOR
 SPECIFIC GRAVITY (H₂O=1): 1.021
 PERCENT VOLATILE BY VOLUME (%): NIL
 EVAPORATION RATE: N/A

N/A = NOT APPLICABLE



24 Madison Road, Fairfield, New Jersey 07004, USA
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,
email: info@jeen.com , Website: www.jeen.com

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): 266°F, PENSKY-MARTENS C.C.
EXTINGUISHING MEDIA: WATER FOG, CARBON DIOXIDE OR DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES: -
UNUSUAL FIRE AND EXPLOSION HAZARDS: -
FLAMMABLE LIMITS: - Lel/Uel: -

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: NOT ESTABLISHED
EFFECTS OF OVEREXPOSURE: MAY CAUSE EYE OR SKIN IRRITATION
EMERGENCY AND FIRST AID PROCEDURES: FLUSH SKIN OR EYES WITH COPIOUS QUANTITIES OF WATER FOR AT LEAST 15 MIN. IN CASE OF EYE CONTACT, GET PROMPT MEDICAL ATTENTION.

SECTION VI - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID: -
INCOMPATIBILITY (MATERIALS TO AVOID: -
HAZARDOUS DECOMPOSITION PRODUCTS: -
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: -

SECTION VII - SPILL OR LEAKAGE PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: FLUSH WITH LARGE AMOUNTS OF WATER.
WASTE DISPOSAL METHOD: INCINERATE.

SECTION VIII- SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFIC TYPE): -
VENTILATION: LOCAL EXHAUST: - SPECIAL: -
MECHANICAL(GENERAL): ACCEPTABLE OTHER: -
PROTECTIVE GLOVES: RUBBER OR PLASTIC
EYE PROTECTION: GOGGLES
OTHER PROTECTIVE EQUIPMENT: EYE WASH AND SAFETY SHOWER

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: -
OTHER PRECAUTIONS: -