

SPECIFICATION SHEET



24 Madison Road, Fairfield, New Jersey 07004, USA  
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,  
email: [info@jeen.com](mailto:info@jeen.com) , Website: [www.jeen.com](http://www.jeen.com)

JEESCREEN OC  
OCTOCRYLENE

APPEARANCE:	LIIGHT AMBER VISCOUS LIQUID
K-VALUE:	34 MINIMUM
COLOR, CVS:	3.0 MAXIMUM
PURITY, GC:	97.0 MINIMUM

Applications/Usage:

Category I UV-B Sunscreen (US) Approved use level (US): up to 10% alone and 7-10% when used in combination with other sunscreen actives. Excellent for water resistant sunscreen products and higher SPF formulations.

Packaging:	Drum			
Weights:	Gross: 256 Lbs.	Tare: 14 Lbs.	Net:	242 Lbs.
	Gross: 116.12 Kgs.	Tare: 6.35 Kgs.	Net:	109.77 Kgs.

Packaging:	Pail			
Weights:	Gross: 38 Lbs.	Tare: 3 Lbs.	Net:	35 Lbs.
	Gross: 17.24 Kgs.	Tare: 1.36 Kgs.	Net:	15.88 Kgs.

***You Can Count On Us!***

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of JEEN International Corporation. The data on this sheet relates only to the specific material designated herein. JEEN International Corporation assumes no legal responsibility for use or reliance upon these data.