



24 Madison Road, Fairfield, New Jersey 07004 USA
Tel: 800-771-JEEN (5336) Tel: 973-439-1401 Fax: 973-439-1402
email: info@jeen.com Website: www.jeen.com

JEESILC PDS-1000

JEESILC PDS-1000 is a 100% active silicone polymer with a viscosity of 1000 centistokes, it is a colorless liquid silicone polymer that is a polydimethylsiloxane. It is used for its chemical stability in antifoams, paint additives, plasticizer in films, cosmetics and hair care products. **JEESILC PDS-1000** is a polydimethylsiloxane.

Typical Properties

	<u>Range</u>	<u>Typical Properties</u>
Appearance:	Clear To Slightly Hazy Liquid	Pass
Acid No. BCP:	0.03 Max.	0.02
Color(APHA):	35 Max.	10
Flash(COC) °F :	600 Min	>650 °F
Specific Gravity@25°C:	0.968-0.974	0.971
Viscosity @ 25 °C:	950-1,050 ctk.	1000
Volatile content:	0.5 Max.	0.05

CAS No. 63148-62-9.

Standard Packaging: Drum
Net Weight: 440 Lbs.

Standard Packaging: Pail
Net Weight: 40 Lbs.

SPECIAL USE AND

SAFE HANDLING INFORMATION: See Material Safety Data Sheet for details. Store in original container in a cool, well-ventilated area.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of JEEN International Corporation. The data on this sheet relates only to the specific material designated herein.

JEEN International Corporation assumes no legal responsibility for use or reliance upon these data.

Revision Date: 3/22/2017