



24 Madison Road, Fairfield, New Jersey 07004, USA
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,
email: info@jeen.com , Website: www.jeen.com

JEESILC PDS-200

JEESILC PDS-200 is a 100% active silicone polymer with a viscosity of 200 centistokes, it is a colorless liquid silicone polymer that is a polydimethylsiloxane. It is used for its chemical stability in antifoams, paint additives, plasticizer in films, cosmetics and hair care products. **JEESILC PDS-200** is a polydimethylsiloxane.

Typical Properties

	<u>Range</u>	<u>Typical</u>
Appearance:	Clear Liquid	Pass
Specific gravity @ 25°C:	0.965-0.971	0.969
Viscosity @ 25 °C:	190-210	200
Color(APHA):	35 Max.	10
Flash(COC) °F:	500 Min. °F	600 °F
Acid No. BCP:	0.03 Max.	0.02
Volatile content:	2.0 Max.	0.5

CAS No. 63148-62-9

Standard Packaging: Drum
Net Weight: 440 Lbs.

Standard Packaging: Pail
Net Weight: 40 Lbs.

SPECIAL USE AND SAFE HANDLING INFORMATION: See Material Safety Data Sheet for details. Store in original container in a cool, well-ventilated area.

You Can Count On Us!

These data are offered in good faith as typical values and not as a Product Specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

01/01/2001