



24 Madison Road, Fairfield, New Jersey 07004, USA
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,
email: info@jeen.com , Website: www.jeen.com

JEESILC PDS-60000

JEESILC PDS-60000 is a 100% active silicone polymer with a viscosity of 60,000 centistokes, it is a colorless liquid silicone polymer that is a polydimethylsiloxane. It is used for its chemical stability in antifoams, paint additives, plasticizer in films, cosmetics and hair care products. **JEESILC PDS-60000** is a polydimethylsiloxane.

Typical Properties

	<u>Range</u>	<u>Typical Properties</u>
Appearance:	Clear Liquid	Pass
Specific Gravity @ 25° C:	0.972-0.980	0.975
Viscosity @ 25° C:	54,000-66,000 ctk.	60,000
Color(APHA):	35 Max.	10
Flash(COC) °F:	500 Min. °F	600 °F
Acid No. BCP:	0.03 Max.	0.01
Volatile content:	2.0 Max.	0.5

CAS No. 63148-62-9.

Standard Packaging: Drum
Net Weight: 425 Lbs.

Standard Packaging: Pail
Net Weight: 40 Lbs.

SPECIAL USE AND SAFE HANDLING INFORMATION: See Material Safety Data Sheet for details. Store in original container in a cool, well-ventilated area.

Important Note: This document is for informational purposes only. Please contact your JEEN International Sales Representative before writing specifications for this product

You Can Count On Us!

These data are offered in good faith as typical values and not as a Product Specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.