



24 Madison Road, Fairfield, New Jersey 07004, USA  
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,  
email: [info@jeen.com](mailto:info@jeen.com) , Website: [www.jeen.com](http://www.jeen.com)

## Material Safety Data Sheet

### Section 1 – Company and Product Identification

Issued by: JEEN International Corporation  
24 MADISON ROAD  
FAIRFIELD, NJ 07004  
Tel#: 973-439-1401

**Chemtrec Emergency Telephone # 800-424-9300**  
**Chemtrec Int'l Tel. # 703-527-3887(Collect Calls Accepted)**

Revision Date: December 13, 2013

Product Name: **JEESILC PDS-60,000**  
Chemical Name: **POLYDIMETHYLSILOXANE**  
Chemical Family: Silicone  
Physical Form: Viscous Liquid  
NFPA Profile: Health – 0 Flammability – 1 Instability/Reactivity – 0

### Section 2 – Hazardous Ingredients/Classification

#### Acute Effects

Eye: Direct contact may cause temporary redness and discomfort  
Skin: No significant irritation expected from a single short-term exposure  
Inhalation: No significant effects expected from a single short-term exposure  
Oral: Low ingestion hazard in normal use.

#### Prolonged/ Repeated Exposure Effects

Skin: No known applicable information  
Inhalation: No known applicable information  
Oral: No known applicable information

#### Signs and Symptoms of Overexposure:

No known applicable information.

#### Medical Conditions Aggravated by Exposure

No known applicable information

\*The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and or expert review of the product. Please refer to section 11 for the detailed toxicology information.

### Section 3 – Composition / Information on Ingredients

None present. This is not a hazardous material as defined in the OSHA Hazard Communication Standard.

### Section 4 – First Aid Measures

Eye: If irritation occurs, flush eye(s) with lukewarm gently flowing water for 5 minutes. Obtain medical attention.  
Skin: No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.  
Inhalation: If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.  
Oral: If irritation or discomfort occurs, obtain medical advice.  
Note to Physician: Treat according to person's condition and specifics of exposure.

### Section 5 – Fire Fighting Measures

Flash point: >610 °F / >321.1 °C (Closed Cup)  
Autoignition: Not determined  
Flammability limits in the air: Not determined  
Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO<sub>2</sub>), dry chemical or water spray. Water can be used to cool fire exposed containers.



24 Madison Road, Fairfield, New Jersey 07004, USA  
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,  
email: [info@jeen.com](mailto:info@jeen.com) , Website: [www.jeen.com](http://www.jeen.com)

#### Section 5 – Fire Fighting Measures Continued

**Firefighting Measures:** Self contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

**Unusual Fire Hazards:** None.

#### Section 6 – Accidental Release Measures

**Containment / Clean up:** Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Section 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Section 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

**Note:** See section 8 for personal protective equipment for spills. Call (973) 439-1401, if additional information is required.

#### Section 7 – Handling and Storage

Use with adequate ventilation. Avoid eye contact. Avoid skin contact.  
Use reasonable care and store away from oxidizing materials.

#### Section 8 – Exposure Controls / Personal Protection

##### **Component Exposure Limits:**

There are no components with workplace exposure limits.

##### **Engineering Controls:**

**Local Ventilation:** None should be needed.  
**General Ventilation:** Recommended

##### **Personal Protective Equipment for Routine Handling:**

**Eyes:** Use proper protection – safety glasses as a minimum.  
**Skin:** Washing at mealtime and end of shift is adequate.  
**Suitable Gloves:** Handle in accordance with good industrial hygiene and safety practices.  
**Inhalation:** No respiratory protection should be needed.  
**Suitable Respirator:** None should be needed.

##### **Personal Protective Equipment for Spills**

**Eyes:** Use proper protection – safety glasses as a minimum.  
**Skin:** Wash at mealtime and end of shift is adequate.  
**Inhalation/Suitable Respirator:** No Respiratory protection should be needed.  
**Precautionary Measures:** Avoid Eye contact. Use reasonable care.  
**Comments:** When heated to temperatures above 150 degrees C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

**Note:** These precautions are for room temperature handling. Use at elevated temperature or aerosol/ spray applications may require added precautions.



24 Madison Road, Fairfield, New Jersey 07004, USA  
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,  
email: [info@jeen.com](mailto:info@jeen.com) , Website: [www.jeen.com](http://www.jeen.com)

#### Section 9 – Physical and Chemical Properties

Physical Form:	Clear Liquid
Color:	Colorless
Odor:	Characteristic Odor
Specific Gravity @ 25°C	0.97
Viscosity	60000 cSt
Freezing/Melting Point:	Not determined
Boiling Point:	>65°C
Vapor Pressure @ 25°C:	Not determined
Vapor Density:	Not determined
Solubility in Water:	Not determined
pH:	Not determined
Volatile Content:	Not determined
Flash Point:	610°F / > 321.1° (closed cup) > 428°F / > 250°C (Cleveland open cup)
Auto ignition Temp:	Not determined
Flammability Limits in Air:	Not determined

#### Section 10 – Stability and Reactivity

Chemical Stability:	Stable
Hazardous Polymerization:	Hazardous polymerization will not occur.
Conditions to avoid:	None

Materials to Avoid: Oxidizing material can cause a reaction.

#### Hazardous Decomposition Products:

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicone dioxide. Formaldehyde.

#### Section 11- Toxicological Information

##### Acute Toxicology Data For Product

	<u>Species</u>	<u>Test Results</u>
Oral LD50:	Rat	>5,000 mg/kg
Dermal LD50:	Rabbit	>2,000 mg/kg

##### Special Hazard Information on Components

No known applicable information

#### Section 12 – Ecological Information

##### Environmental Fate and Distribution

Air:	This product is a high molecular weight liquid polymer which has a very low vapor pressure (<1 mmHg). As a result, it is unlikely to become an atmospheric contaminant unless generated as an aerosol.
Water:	This product has a very low water solubility (<100 ppb.). As it has a specific gravity of <1, if discharge to water, it will initially form a surface film. As the product is non-volatile and has a high binding affinity for particulate matter, it will absorb to particulates and sediment out.
Soil:	If discharge to surface water, this product will bind to sediment. If discharged in effluent to a waste water treatment plant, the product is removed from the aqueous phase by binding to sewage sludge. If the sewage sludge is subsequently spread on soil, the silicone product is expected to degrade.
Degradation:	This product, polydimethylsiloxane, degrades in soil abiotically to form smaller molecules. These in turn are either biodegraded in soil or volatilized into the air where they are broken down in the presence of sunlight. Under appropriate conditions, the ultimate degradation products are inorganic silica, carbon dioxide and water vapor. Due to the very low water solubility of this product, standard OECD protocols for ready and inherent biodegradability are not suitable for measuring the biodegradability of this product. The product is removed >80% during the sewage treatment process.



24 Madison Road, Fairfield, New Jersey 07004, USA  
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,  
email: [info@jeen.com](mailto:info@jeen.com) , Website: [www.jeen.com](http://www.jeen.com)

## Section 12 – Ecological Information Continued

### Environmental Effects

Toxicity to water Organisms: Based on analogy to similar materials this product is expected to exhibit low toxicity to aquatic organisms.

Toxicity to soil Organisms: Experiments show that when sewage sludge containing polydimethylsiloxane is added to soil, it has no effect on soil micro-organisms, earthworms or subsequent crops grown in the soil.

Bioaccumulation: This product is a liquid and is a high molecular weight polymer. Due to its physical size it is unable to pass through, or be absorbed by biological membranes. This has been confirmed by testing or analogy with similar products.

### Fate and Effects in Waste Water Treatment Plants

This product or similar products has been shown to be non-toxic to sewage sludge bacteria.

### ECOTOXICITY CLASSIFICATION CRITERIA

Hazard Parameters (LC50 OR EC 50)	HIGH	MEDIUM	LOW
Acute Aquatic Toxicity (mg/l)	$\leq 1$	$>1$ and $\leq 100$	$>100$
Acute Terrestrial Toxicity	$\leq 100$	$>100$ and $\leq 2000$	$>2000$

\*This table is adapted from "Environmental Toxicology and Risk Assessment" ASTM STP 1179, P.34, 1993.

\*This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

## Section 13 – Disposal Considerations

RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989)-469-6315, if additional information is required.

## Section 14 – Transport Information

### DOT Road Shipment Information (49 CFR 172.101)

No subject to DOT

### Ocean Shipment (IMDG)

Not subject to IMDG code

### Air Shipment (IATA)

Not subject to IATA regulations.

## Section 15- Regulatory Information

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA inventory of Chemical Substances.

### EPA SARA Title III Chemical Listings

#### Section 302 Extremely Hazardous Substances (40 CFR 355):

None



24 Madison Road, Fairfield, New Jersey 07004, USA  
Tel: 800-771-JEEN (5336), Tel: 973-439-1401, Fax: 973-439-1402,  
email: [info@jeen.com](mailto:info@jeen.com) , Website: [www.jeen.com](http://www.jeen.com)

Section 15- Regulatory Information Continued

**Section 304 CERCLA Hazardous Substances (40 CFR 302):**

None

**Section 311/312 Hazard Class (40 CFR 370)**

Acute: No  
Chronic: No  
Fire: No  
Pressure: No  
Reactive: No

**Section 313 Toxic Chemicals (40 CFR 372):**

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

**Supplemental State Compliance Information**

**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

**Massachusetts:**

No ingredient regulated by MA Right-to-Know Law present

**New Jersey**

<u>CAS Number</u>	<u>Wt%</u>	<u>Component Name</u>
63148-62-9	>60.0	Polydimethylsiloxane

**Pennsylvania**

<u>CAS Number</u>	<u>Wt%</u>	<u>Component Name</u>
63148-62-9	>60.0	Polydimethylsiloxane

Section 16- Other Information

**Disclaimer:** As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with applicable federal, state and local regulations remains the responsibility of the user