

Revision Date: November 11, 2017 Version No.: 3

SECTION 1 - IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product Identifier

Product Name JEESPERSE CPW-2-PS11

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Identified uses Cosmetic raw material

1.3 Details of the Supplier of the Safety Data Sheet

Company JEEN International Corporation

24 Madison Road

Fairfield, New Jersey 07004 Tel: +1-973-439-1401 Fax: +1-973-439-1402 email: info@jeen.com

Website: www.jeen.com

1.4 Emergency telephone number

+1703-527-3887(Chemtrec Int'l Tel - Collect calls accepted)

SECTION 2 – HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture according to Regulation (EC) 1272/2008

None

2.2 Label Elements according to Regulation (EC) EU 1272/2008

Hazard pictogramNoneSignal wordsNoneHazard statementsNonePrecautionary statementsNone

2.3 Other Hazards None known

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances -

3.2 Mixture

Chemical characterization Cosmetic ingredients

Polyslicone-11 INCI Polyethylene Sodium Polyacrylate 9002-88-4 63394-02-5 CAS 9003-04-7 EC Polymer Exempt Polymer Exempt Polymer Exempt Concentration 51.8-55.8% 22.1-24.1% 21.1-25.1%

SECTION 4 – FIRST AID MEASURES

4.1 Description of First Aid Measures

Inhalation:

Not expected to be a problem under normal conditions of use.

When finely divided, inhalation of dust may cause irritation of

mucous membrane and respiratory tract. OSHA permissible

JEESPERSE CPW-2-PS11 Page 1 of 5



Revision Date: November 11, 2017 Version No.: 3

Skin and Eye Contact:

Ingestion:

5.3

Emergency and First Aid Procedures:

exposure limit (PEL-TWA) and ACGIH threshold limit value (TLV-TWA) for respirable dust: 5 mg/m3. Total nuisance dust OSHA PEL-TWA: 15 mg/m3; total dust ACGIH TLV-TA: 10 mg/m3. If heated to decomposition, fumes generated may result in respiratory irritation. ACGIH exposure limit for paraffin wax fume is a TLV-TWA of 2 mg/m3.

Not expected to be a problem under normal conditions of use. May produce mild irritation on prolonged contact with skin or eyes. Not expected to be absorbed through the skin in significant quantities. The cool solid material is not expected to cause skin or eye irritation; however, contact with molten material may result in thermal burns.

May be harmful if swallowed. May cause gastrointestinal disturbances.

Wash skin thoroughly with soap and water. Launder clothing before reuse. If in eyes, irrigate with flowing water immediately and continuously for fifteen minutes. Consult a physician. If inhaled, remove to fresh air and administer oxygen if necessary. If ingested, consult a physician. If molten polymer gets on skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention for thermal burns.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 Flash Point: > 350°F (> 175 °C) Flammable Limits: Not available Flash Method: COC ASTM D-92

5.2 Extinguishing Media Use water spray or fog, alcohol-type foam, dry chemical, or CO2.

Fire Fighting Procedures

Use a self-contained breathing apparatus with full face piece operate in pressure-demand or other positive pressure mode. Non-flammable. Keep fire-exposed containers cool using water spray.

5.4 Unusual Fire and Explosion Hazards When finely divided and suspended in air, this product could be

flammable. Under these circumstances, keep away from heat, sparks and open flames. Use adequate ventilation and ground all equipment. As with most solid or particulate organic materials, extremely high dust concentration in air may result in a potential explosion hazard. Use good housekeeping to prevent significant

solids accumulation.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

6.1 Methods and Material for Containment and Cleaning Up

Sweep up material and place in appropriate disposal container. Use sweeping compound or other cleaning aids to pick up residues. Wash down area thoroughly with water. Use appropriate personal protective equipment as necessary. If liquid is hot, attempt to confine spill and let the liquid solidify. Once solid, the product may be recovered as any other solid material. When disposing, secure

JEESPERSE CPW-2-PS11 Page 2 of 5



Revision Date: November 11, 2017 Version No.: 3

container and take to an approved waste disposal site. Dispose of residues in accordance with applicable Local, State and Federal Regulations.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

The shelf life of the products depends on storage conditions and intended uses; properties such as melting point, viscosity, and penetration will remain stable for over one year. The color of the products, especially white waxes, may darken slightly after two or three months under certain conditions. Care must be taken to avoid overheating the molten wax and causing oxidation of the product. Care must be taken to avoid overheating the molten wax and causing oxidation of the product. Care must also be taken to avoid skin contact with the molten wax, which will cause thermal burns. Good hygiene practices should always be followed when handling the material.

7.2 Condition for Safe Storage, including any Incompatibilities

Packaged material (boxes, bags) should be stored in a cool, dry place at or below room temperature.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Personal Protective Equipment

Respiratory Protection: Respirator use is not expected to be necessary under normal

conditions of handling. In emergency situations, use of a NIOSH-

approved respirator may be required.

Ventilation: General ventilation should be provided to maintain ambient

concentrations below nuisance levels.

Protective Clothing: Chemical-resistant gloves and chemical goggles should be used to

prevent skin and eye contact.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic Physical and Chemical Properties

Appearance White Powder
Melt Point, °C 40 - 55°C
Color White to Light Tan

5% Aqueous Solution Disperses

SECTION 10 - STABILITY AND REACTIVITY

10.1 Stability Stable [X] under Normal conditions of storage and use. Unstable []

10.2 Incompatible Materials Keep away from strong oxidizing agents

10.3 Hazardous Decomposition Products None known.

10.4 Hazardous Polymerization May occur [] Will not occur [X]

JEESPERSE CPW-2-PS11 Page 3 of 5



Revision Date: November 11, 2017 Version No.: 3 **Conditions to Avoid** 10.5 See above statements. SECTION 11 - TOXICOLOGICAL INFORMATION 11.1 Information on Toxicological Effects There are no known toxicological effects. SECTION 12 - ECOLOGICAL INFORMATION 12.1 Information on Ecological Effects This product would not be expected to cause damage to the environment. It would be expected to biodegrade slowly, depending upon the conditions to which it is exposed. Under OECD Method 301D, the biodegradability is less than 25% after 5 days. **SECTION 13 - DISPOSAL CONSIDERATIONS** 13.1 **Waste Treatment Methods** Surplus or waste residues of this product should be placed in a suitable waste container and taken to an approved waste disposal site. Dispose of all surplus or waste residues in accordance with

SECTION 14 – TRANSPORTATION INFORMATION

^{***}Required*** TRANSPORT AT OR BELOW 72'F****

UN Number:	Not hazardous*	IMDG Page Number:	Not applicable
UN Class:	Not applicable	TREMCARD Number:	Not applicable
ADR/RID Class:	Not applicable	IFAG Table Number:	Not applicable
EmS Number:	Not applicable		

applicable waste management regulations.

Department of Transportation: DOT Classification: Not Regulated

IATA Class: Not Regulated by IATA

IMDG: Non-Regulated Material (Non Hazardous)

SECTION 15 - REGULATORY INFORMATION

EC Classification: Not classified under 67/548/EEC

Hazard Symbol: None H Statements: None P Statements: None

This product has no status under food additive regulations. This product does not contain any chemicals listed in Section 313 of the Superfund Act and Reauthorization Amendment (SARA 313) or the Clean Air Act Amendments (CAA). No ozone-depleting chemicals are contained or used in the manufacture of this product.

JEESPERSE CPW-2-PS11 Page 4 of 5

^{*}For material shipped at or above 100°C and below its flash point, the following UN class, number applies: Elevated Temperatures NOS, Hazard Class 9, PG III, ID#: 3257



Revision Date: November 11, 2017 Version No.: 3

SECTION 16 – OTHER INFORMATION

Health (NFPA): 0 Flammability (NFPA): 1 Reactivity (NFPA): 0 Protective Equipment: B

Disclaimer: As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with applicable federal, state and local regulations remains the responsibility of the user

JEESPERSE CPW-2-PS11 Page 5 of 5