



SAFTY DATA SHEET
According to Regulation (EC) No 1907/2006 (REACH)

Revision Date: March 8, 2017

Version No.: 2

SECTION 1 – IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

- 1.1 Product Identifier**
Product Name **JEESPERSE ICE-T-GCS-21**
- 1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against**
Identified uses **Cosmetic raw material**
- 1.3 Details of the Supplier of the Safety Data Sheet**
Company **JEEN International Corporation**
24 Madison Road
Fairfield, New Jersey 07004
Tel: +1-973-439-1401
Fax: +1-973-439-1402
email: info@jeen.com
Website: www.jeen.com
- 1.4 Emergency telephone number** **+1703-527-3887(Chemtrec Int'l Tel - Collect calls accepted)**

SECTION 2 – HAZARDS IDENTIFICATION

- 2.1 Classification of the Substance or Mixture** according to Regulation (EC) 1272/2008
None
- 2.2 Label Elements** according to Regulation (EC) EU 1272/2008
Hazard pictogram **None**
Signal words **None**
Hazard statements **None**
Precautionary statements **None**
- 2.3 Other Hazards** **None known**

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

- 3.2 Mixture**
INCI: **Stearic Acid, Cetyl Stearyl Alcohol, Glyceryl Stearate (and) PEG-100 Stearate, Acrylates/C10-30 Alkyl Acrylate Crosspolymer**
CAS: **57-11-4, 67762-27-0, 123-94-4, 9004-99-3**

SECTION 4 – FIRST AID MEASURES

- 4.1 Description of First Aid Measures**
Inhalation: **Not expected to be a problem under normal conditions of use. When finely divided, inhalation of dust may cause irritation of mucous membrane and respiratory tract. OSHA permissible exposure limit (PEL-TWA) and ACGIH threshold limit value (TLV-TWA) for respirable dust: 5 mg/m3. Total nuisance dust OSHA PEL-TWA: 15 mg/m3; total dust ACGIH TLV-TA: 10 mg/m3. If**



SAFETY DATA SHEET
According to Regulation (EC) No 1907/2006 (REACH)

Revision Date: March 8, 2017

Version No.: 2

Skin and Eye Contact:	heated to decomposition, fumes generated may result in respiratory irritation. ACGIH exposure limit for paraffin wax fume is a TLV-TWA of 2 mg/m ³ . Not expected to be a problem under normal conditions of use. May produce mild irritation on prolonged contact with skin or eyes. Not expected to be absorbed through the skin in significant quantities. The cool solid material is not expected to cause skin or eye irritation; however, contact with molten material may result in thermal burns.
Ingestion:	May be harmful if swallowed. May cause gastrointestinal disturbances.
Emergency and First Aid Procedures:	Wash skin thoroughly with soap and water. Launder clothing before reuse. If in eyes, irrigate with flowing water immediately and continuously for fifteen minutes. Consult a physician. If inhaled, remove to fresh air and administer oxygen if necessary. If ingested, consult a physician. If molten polymer gets on skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention for thermal burns.

SECTION 5 – FIRE FIGHTING MEASURES

- | | | | |
|------------|---|---|---------------|
| 5.1 | Flash Point: > 350°F (> 175 °C)
Flash Method: | Flammable Limits: | Not available |
| 5.2 | Extinguishing Media | CO ₂ ASTM D-92 | |
| 5.3 | Fire Fighting Procedures | Use water spray or fog, alcohol-type foam, dry chemical, or CO ₂ . | |
| 5.4 | Unusual Fire and Explosion Hazards | Use a self-contained breathing apparatus with full face piece operate in pressure-demand or other positive pressure mode. Non-flammable. Keep fire-exposed containers cool using water spray. | |
| | | When finely divided and suspended in air, this product could be flammable. Under these circumstances, keep away from heat, sparks and open flames. Use adequate ventilation and ground all equipment. As with most solid or particulate organic materials, extremely high dust concentration in air may result in a potential explosion hazard. Use good housekeeping to prevent significant solids accumulation. | |

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- | | | |
|------------|---|--|
| 6.1 | Methods and Material for Containment and Cleaning Up | Sweep up material and place in appropriate disposal container. Use sweeping compound or other cleaning aids to pick up residues. Wash down area thoroughly with water. Use appropriate personal protective equipment as necessary. If liquid is hot, attempt to confine spill and let the liquid solidify. Once solid, the product may be recovered as any other solid material. When disposing, secure container and take to an approved waste disposal site. Dispose of residues in accordance with applicable Local, State and Federal Regulations. |
|------------|---|--|



SAFTY DATA SHEET
According to Regulation (EC) No 1907/2006 (REACH)

Revision Date: March 8, 2017

Version No.: 2

SECTION 7 – HANDLING AND STORAGE

- | | |
|--|---|
| 7.1 Precautions for Safe Handling | The shelf life of the products depends on storage conditions and intended uses; properties such as melting point, viscosity, and penetration will remain stable for over one year. The color of the products, especially white waxes, may darken slightly after two or three months under certain conditions. Care must be taken to avoid overheating the molten wax and causing oxidation of the product. Care must be taken to avoid overheating the molten wax and causing oxidation of the product. Care must also be taken to avoid skin contact with the molten wax, which will cause thermal burns. Good hygiene practices should always be followed when handling the material. |
| 7.2 Condition for Safe Storage, including any Incompatibilities | Packaged material (boxes, bags) should be stored in a cool, dry place at or below room temperature. |

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

- | | |
|---|--|
| 8.1 Personal Protective Equipment
Respiratory Protection:

Ventilation:

Protective Clothing: | Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required.
General ventilation should be provided to maintain ambient concentrations below nuisance levels.
Chemical-resistant gloves and chemical goggles should be used to prevent skin and eye contact. |
|---|--|

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|--|--|
| 9.1 Information on basic Physical and Chemical Properties
Appearance
Melt Point, °C | White to Light Tan Powder
45 - 55°C |
|--|--|

SECTION 10 – STABILITY AND REACTIVITY

- | | |
|--|---|
| 10.1 Stability | Stable [X] under Normal conditions of storage and use. Unstable [] |
| 10.2 Incompatible Materials | Keep away from strong oxidizing agents |
| 10.3 Hazardous Decomposition Products | None known. |
| 10.4 Hazardous Polymerization | May occur [] Will not occur [X] |
| 10.5 Conditions to Avoid | See above statements. |



SAFTY DATA SHEET
According to Regulation (EC) No 1907/2006 (REACH)

Revision Date: March 8, 2017

Version No.: 2

SECTION 16 – OTHER INFORMATION

Health (NFPA): 0 Flammability (NFPA): 1 Reactivity (NFPA): 0 Protective Equipment: B

Disclaimer: As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with applicable federal, state and local regulations remains the responsibility of the user